



WWW.TITANLEDUS.COM

# Product Specification Sheet Titan LED 1 Channel LED Driver

\*Designed To Be Used Exclusively with The Titan LED Hennessy Series Linear 8 Foot Tube Light



TITAN LED SKU# 17-1CH-DR1100-ND

## \*ATTENTION:

Titan LED USA Tubes USE A SPECIFICALLY ENGINEERED EXTERNAL LED DRIVER To OPERATE. Providing Clean, Surge Protected, I/C Monitored, Constant Current Power is Crucial to the longevity of the Light Emitting Diodes.



**RoHS**  
COMPLIANT  
2002/95/EC



## Features: (Input Voltage 100 - 277V)

- 1 Channel direct constant current output
- Titan LED Tube light - locking quick connector
- IP-66 Rated (Suitable for damp locations)
- Class 2 Constant Current Output
- High Efficiency
- Active Power Factor Correction
- Non Dimmable
- Mounting tabs (1 on each end)
- Non conductive Polycarbonate housing
- Over Voltage Protection
- Shock and Vibration resistant
- EMC Compliance
- Short Circuit Protection
- Over Temp protection
- Universal voltage capabilities
- FCC Compliance
- Meets VDE standards
- No noise
- UL Listed

Output Current:	1100 mA
Output Voltage:	18 - 36 Volts direct constant current
Max. Output:	40 Watts
Output CH:	1 - Channel
Type:	Constant Current
Power Factor:	0.94
Input Voltage AC:	100 - 277 Volts AC
Input Current:	0.53 A Maximum
Input Frequency:	50/60 Hz
Efficiency:	88%
THD:	8.4%
Protection:	Short Circuit / Over Temperature
Over Voltage Protection:	280 VAC
Dimensions:	3.8"L x 3.8"W x 1.3"H
Dimming:	No
Operating Temperature:	-20 °C - +60 °C
Working Humidity:	Relative 20 - 85%
Net Weight:	.92 lbs / 0.41 kg

**TITAN LED** 850 East Covey Lane, Bldg. C, Suite 140, Phoenix, AZ 85024

Phone: (632) 552-7065 Fax: (805) 523-7502

Attention: All specifications are subject to change without notice.

All Images and Information are Property of Titan LED Inc. 2019 and may Only be used by permission.